Basic Information

. Place of Origin: China Brand Name: **XWELL**

· Certification: UN38.3,MSDS,UL,CB,BIS,PSE,GB4943.1

safety standard, CE, FCC, ROHS, battery UN38.3, MSDS, UL, CB, BIS, PSE

Model Number: XW-600W-01

Minimum Order Quantity: 1 pcs Packaging Details: Carton

. Delivery Time: 7-10 working days

L/C, D/A, D/P, T/T, Western Union, • Payment Terms:

MoneyGram

. Supply Ability: 5000 pcs per month



Product Specification

• Ouput: 600W Full Capacity: 460Wh . Cylcle Life: > 2000

. Charge Input: DC5521 12-24V-5Am, PD 100W

• AC Output: AC220V/50Hz

2 * QC3.0 MAX 18 W 12V / 1.5A; SCP . USB Output:

Maximum Output Power: Maximum 22.5W

• Type-C Output: PD 100W Output

Batteries: LiFePO4 Battery / 3400mAh

. Charging Parameters: DC 12-24V / 5A

. LCD Display: Battery Percentage And Battery Column

• Highlight: 460Wh Portable Lithium Battery Power Station,

600W Portable Lithium Battery Power Station, Emergency portable power station 600w

Our Product Introduction

Product Description

600W 460Wh Portable Lithium Battery Power Station ESS Lithium Battery Solar Power System Supply Solar

This XW-600W energy storage system (ESS) is a technology that allows for the capture, storage, and subsequent release of energy for use when needed. It plays a crucial role in balancing energy supply and demand, especially in situations where renewable energy sources like solar and wind are intermittent in nature. Energy storage systems are employed in various sectors, including power grids, transportation, industrial processes, and residential applications.


Benefits of ESS battery

- 1. Grid Stability and Reliability: ESS can store excess energy during periods of low demand and release it during peak demand, helping to stabilize the electricity grid and prevent blackouts or brownouts.
- 2. Renewable Energy Integration: Since renewable sources like solar and wind are variable, ESS can store excess energy generated during sunny or windy periods and supply it when those sources are not producing.
- 3. Load Shifting: ESS enables shifting energy consumption from peak to off-peak hours, which can lead to cost savings by utilizing cheaper electricity rates during non-peak times.
- **4. Backup Power:** ESS can provide backup power during grid outages, critical for maintaining essential services in places like hospitals, data centers, and emergency facilities.

Specification

Category	Project	Specifications
INTPUT	DC input	DC5521 12-24V-5A
	DC input	PD 100W
AC OUT 220V	AC output voltage	1 port, AC220V±5%
	AC output power	600W
	AC output over power protection	650W Approximately
	AC output waveform	pure sine wave
	AC output peak	1200W Peak maintenance time <50ms
	frequency	50Hz
USB output port	USB1 output	QC3.0 MAX 18 W 12V / 1.5A ; SCP maximum output power: maximum 22.5W
	USB2 output	QC3.0 MAX 18 W 12V / 1.5A ; SCP maximum output power: maximum 22.5W
	TYPE-C1 output	PD / QC3.0 MAX 30W 12V/2.5A
DC12V output	DC1 DC2 output	12V / 10A MAX
TYPE-C output/input	TYPE-C2	PD 100W output
Batteries	type	LiFePO4 battery / 3400mAh
	capacity	23.8Ah (6S7P)
	power	460Wh
	cycle life	1000+ times
Charging parameters		DC 12-24V / 5A
charging time	5 - 6H	Charge from 0% to 100% (automatic cut-off)
Full voltage	21.9V ±0.1V	The voltage when the battery is charged to the automatic cut-off
LCD display	Display power; charging, stop charging status	Battery percentage and battery column display
	DC, AC, inverter status	The display shows
boot static		<10W
Protective function		Short circuit, overload, over temperature, over voltage, over current, under voltage, etc.
over temperature protection	over temperature protection	≥85
	over temperature recovery	≤70

Front pannel



- 1 → DC12V/10A(DC5521) × 2 2 → USB QC3.0 × 2 3 → TYPE-C1 30W × 1 4 → TYPE-C2 PD100W I/O × 1 5 → AC ouput 220V/600W × 1
- 6 DC5521 12-24V/5A × 1
 7 Diplay screen × 1
 8 LED light × 1
 9 Switch × 5
 10 Car charger × 1

Product accessories



Product Accessories



Usage time for common devices





The use time data is for reference only.

Different equipment and use methods will lead different usage times.

Our services

- 1. Your inquiry related to our products price will be replied in 24 hours.
- 2. Experienced staffs to answer all your enquiries in fluent English
- 3. We make the OEM and ODM service for more than 5 years
- 4. Protection of your sales area, ideas of design and all your private information.
- 5. No matter big order or small order, we will provide all the best quality, best service.
- 6. If our products have any problem that we caused, they will be sent free in the next order.



XWELL GUANGDONG XWELL TECHNOLOGY CO., LTD.

+86 18620492985

sales@esslithiumbattery.com esslithiumbattery.com

Room 322, Building 3, No. 801, Qiaoxing Avenue, Xiaoluo Village, Shatou Street, Panyu District, Guangzhou, China