



## 2.56kwh 5.12kwh 10.24kwh 200a Rack-mounted Home Energy Storage battery Rackmount Lithium Battery

### Our Product Introduction

#### Basic Information

- Place of Origin: China
- Brand Name: XWELL
- Certification: UN38.3, MSDS, UL, CB, BIS, PSE, GB4943.1 safety standard, CE, FCC, ROHS, battery UN38.3, MSDS, UL, CB, BIS, PSE
- Model Number: XW-2560W-1
- Minimum Order Quantity: 1 pcs
- Packaging Details: Carton
- Delivery Time: 7-10 working days
- Payment Terms: L/C, D/A, D/P, T/T, Western Union, MoneyGram
- Supply Ability: 5000 pcs per month



#### Product Specification

- Standard Voltage: 51.2V
- Capacity: 2.56kwh 5.12kwh 10.24kwh
- Communication Interface: RS485, RS232, CAN
- Energy: 2.56kwh
- Cell Model: LiFePO4 Prismatic
- Cycle Life: >6000 Cycles(80%DOD)
- Discharge Current: 50A
- Max Charge Current: 50A
- Discharge Cut-off Voltage: 51.2V
- Highlight: 2.56kwh Rackmount Lithium Battery,  
5.12kwh Rackmount Lithium Battery,  
10.24kwh Rackmount Lithium Battery

## Product Description

### 2.56kwh 5.12kwh 10.24kwh 200a Rack-mounted Home Energy Storage battery Rackmount Lithium Battery

#### Rack-mounted energy storage (Home/Industrial)

The series features A-grade lithium iron phosphate cells with a cycle life of over 3000 times, built-in BMS for safety protection, and supports RS485/RS232/CAN communication protocols. The series is also compatible with various energy storage inverters on the market, providing stable energy storage and output.

#### Good Quality -- ISO9001:2019 Standard


37 production processes and 7 steps quality check to promise stable quality for you. Xwell has very strictly quality control system including incoming materials control, in-process quality control and outgoing quality control.

We do 100% full quality check and aging test to ensure product quality.

#### Rackmount Lithium Battery Specification

Model	51.2V50Ah	51.2V100Ah	51.2V200Ah
Nominal voltage	51.2V		
Nominal capacity (kwh)	2.56	5.12	10.24
Cell type	LiFePO4		
Standard charge voltage	54.6V(adjustable)		
Max charge current	50A		
Discharge cut-off voltage	42.5V(adjustable)		
Max discharge current	50A		
Display	LCD(Optional)		
Communication interface	CAN/RS485/RS232		
Cycle life	>6000 Cycles (80%DOD)		
Charge temperature range	0~45°C		
Discharge temperature range	-20~60°C		
Color	Black		
Dimension (mm)	442x410x133 3U	442x410x177 4U	550x442x220 5U
Weight	About 35Kg	About 42Kg	About 84Kg
Installation method	Rack Mount		

#### Cell Specification of Rackmount Lithium Battery



#	Item	Parameter
A	Height	119±1.0 mm
B	Width	160±1.0 mm
C	Thickness	≤50 mm
D	Tabs Distance	97±0.5 mm

#### Operation Pannel of Rackmount Lithium Battery



### Size of Rackmount Lithium Battery



### Structure of Rackmount Lithium Battery



#	Item	Material
(1)	Case Cover	SPCC
(2)	Case Hanger	SPCC
(3)	Insulation Sheet	Ethoxyline
(4)	Bus-Bar	Aluminum Alloy
(5)	Battery Cell	LFP, Aluminum Shell
(6)	Module Side Plate	ABS / PC
(7)	Cell Binding Loop	Plastic Steel
(8)	Case Bottom	SPCC
(9)	Insulating Wiring Terminal	Bakelite
(10)	Side Plate Combination Board	SPCC
(11)	BMS	PCB
(12)	Commination Board	PCB
(13)	DC Switch	/
(14)	Handle	Sherardized SPCC
(15)	Case Front Cover	SPCC
(16)	Terminal Bar (+ & -)	/

### Application of Rackmount Lithium Battery

## Application Scenario



Data Center



C&I Park



Telecom Base



Medical Equipment

### FAQ

1. Is the battery used in the battery pack grade A?

Yes, we only use Grade A and Brand new cells inside.

2. Do you test and match the battery before installing the battery pack?

Yes, every cell will be tested capacity, IR, voltage to surely match

Voltage: The deviation less than 0.01V

Resistance: The deviation less than 0.1mΩ

Capacity: Same capacity matched

3. How do I store my batteries?

When the product is not in use for a long time, it should be stored in a dry, clean and well-ventilated warehouse at 10°C 35°C, avoiding inflammable and explosive materials; the battery pack should be charged and maintained regularly every three months to ensure that the battery best performance state.

4. What is the cycle life of the battery?

6000 cycle life @ 80% DOD

5. What's the warranty of your 48V/51.2V battery pack?

5 years warranty, if there is broken item under quality problem within warranty time, we will offer free replacements or refund, up to your needs

6. Do your batteries support series or parallel connection?

Our 48V battery packs support up to 15pcs in parallel, if you need series connection, please contact our sales staff



**XWELL** GUANGDONG XWELL TECHNOLOGY CO., LTD.



+86 18620492985



[sales@esslithiumbattery.com](mailto:sales@esslithiumbattery.com)



[esslithiumbattery.com](http://esslithiumbattery.com)

Room 322, Building 3, No. 801, Qiaoxing Avenue, Xiaoluo Village, Shatou Street, Panyu District, Guangzhou,  
China